
المد				53.00 ±0.38							<b>–</b>					
12.60 ±0.38	±0.25				47.04 ±0.25											
2.60	8.36 ±0.25	2.84					_			38	.96	3		_		
_							_	_	_	_						
			-	Q		f.	<b>+</b>	• • • •		• •	。。 	。。	• •	<u>:</u> ]	©	
1						-	Ī			2.7	7					J
					_		\			38						




UNLESS O	TOLERANCE UNLESS OTHERWISE SPECIFIED				
.X	±0.25				
XX	+0.13				


.XXX ±0.10

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ORIGINAL (1)





## NOTES:

MATERIAL:

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0

SHELL: STEEL, TIN PLATED

CONTACT: COPPER ALLOY, 15µ GOLD PLATED

OPERATING TEMPERATURE: -55°C to +85°C

CURRENT RATING: 3A PER CONTACT CONTACT RESISTANCE:  $25m\Omega$  MAX. INSULATOR RESISTANCE:  $5000M\Omega$  min.

**DIELECTRIC** 

WITHSTANDING VOLTAGE: 1000V AC rms

## 627 SERIES D-SUB CONNECTOR





THESE DRAWINGS AND SPECIFICATIONS
ARE THE PROPERTY OF EDAC INC.,AND
SHALL NOT BE REPRODUCED,OR COPIED
OR USED AS THE BASIS FOR THE
MANUFACTURE OR SALE OF APPARATUS
WITHOUT WRITTEN PERMISSION.

	SW REFERENCE NO.: 627 ASSEMBLY									
	DRAWN: C.B	DATE: AUG. 01/2018								
	CHECKED:	DATE:								
	SCALE: 1:1	SHEET 1 OF 1								
	DRAWING NUMBER: 627-025-3	320-247 ISSUE								

DRAWING NUMBER: 627-025-320-247 ISSUE
PART NUMBER: 627-025-320-247 1