


| UNLESS O | TOLERANCE<br>JNLESS OTHERWISE<br>SPECIFIED |  |
|----------|--|--|
| .X       | ±0.25                                      |  |
| .XX      | ±0.13                                      |  |


.XXX ±0.10

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ORIGINAL 1





## NOTES:

MATERIAL:

HOUSING: BLUE THERMOPLASTIC POLYESTER, UL94V-0

SHELL: STEEL, NICKEL PLATED

CONTACT: COPPER ALLOY, GOLD FLASH PLATED

OPERATING TEMPERATURE: -55°C ~ 125°C

CURRENT RATING: 5A PER CONTACT


CONTACT RESISTANCE:  $25m\Omega$  MAX. INSULATOR RESISTANCE:  $5000M\Omega$  min.

**DIELECTRIC** 

WITHSTANDING VOLTAGE: 1000V AC rms

|           | _   |
|-----------|-----|
|           |     |
|           | ) - |
| COMPLIANT |     |

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.





THESE DRAWINGS AND SPECIFICATIONS
ARE THE PROPERTY OF EDAC INC.,AND
SHALL NOT BE REPRODUCED, OR COPIED
OR USED AS THE BASIS FOR THE
MANUFACTURE OR SALE OF APPARATUS
WITHOUT WRITTEN PERMISSION.

| SW REFERENCE NO.: 62 | 27 ASSEMBLY        |
|----------------------|--------------------|
| DRAWN: C.B           | DATE: AUG. 01/2018 |
| CHECKED:             | DATE:              |
| SCALE: 1:1           | SHEET 1 OF 1       |
|                      |                    |

 DRAWING NUMBER:
 627-M09-220-LN6
 ISSUE

 PART NUMBER:
 627-M09-220-LN6
 1