



| TOLERANCE UNLESS OTHERWISE SPECIFIED | | |
|--|-------|--|
| X. | ±0.25 | |
| .XX | ±0.13 | |
| .XXX | ±0.10 | |

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER ORIGINAL





NOTES:

MATERIAL:

HOUSING: BLUE THERMOPLASTIC POLYESTER, UL94V-0

SHELL: STEEL, NICKEL PLATED

CONTACT: COPPER ALLOY, 15µ GOLD PLATED

OPERATING TEMPERATURE: -55°C ~ 125°C

CURRENT RATING: 5A PER CONTACT

CONTACT RESISTANCE: $25m\Omega$ MAX. INSULATOR RESISTANCE: 5000MΩ min.

DIELECTRIC

WITHSTANDING VOLTAGE: 1000V AC rms

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE

627 SERIES D-SUB CONNECTOR

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

| SCALE: 1:1 | SHEET 1 OF 1 |
|--------------------------------|--------------------|
| CHECKED: | DATE: |
| DRAWN: C.B | DATE: AUG. 01/2018 |
| SW REFERENCE NO.: 627 ASSEMBLY | |

627-M37-320-LN1 ISSUE DRAWING NUMBER: PART NUMBER: 627-M37-320-LN1