

TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER
ORIGINAL

(1)





	- 6.10
	11.00

NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

OPERATING TEMPERATURE:

 .X
 ±0.25

 .XX
 ±0.13

 .XXX
 ±0.05

POWER/CO-AX CONTACT RATING:20A (CURRENT)(IF PRESENT)SIGNAL CONTACT CURRENT RATING:5A PER CONTACTSIGNAL CONTACT RESISTANCE:10mΩ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 5000MΩ min.


-55°C ~ 125°C

1000V AC rms

THERMOPLASTIC POLYESTER, UL94V-0

COPPER ALLOY, GOLD FLASH PLATED

STEEL, NICKEL PLATED



	SW REFERENCE NO.: 629 COMBO ASSEMBLY			
COMBINATIO	DRAWN: C.B	DATE: JAN. 01/20	19	
			DATE:	
EDAC INC TORONTO, ONTARIO CANADA	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
		DRAWING NUMBER: 629-11W	1240-2NB	ISSUE
YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 629-11W	1240-2NB	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

