






ISSUE NUMBER
ORIGINAL







NOTES:

1. MATERIALS:

INSULATOR: LCP, BLACK, UL 94V-0

CONTACT: PHOSPHOR BRONZE (T=0.3mm), SELECT GOLD FLASH PLATING ON CONTACT AREA

TIN ON TAILS OVER NICKEL

 SHELL:
 BRASS (T=0.2mm)

 2. VOLTAGE RATING:
 125 VAC RMS

 3. CURRENT RATING:
 1.5 AMPS @25°C

 4. CONTACT RESISTANCE:
 20mΩ MAX

5. INSULATOR RESISTANCE: $1000 \text{ M}\Omega \text{ MIN } \textcircled{0} 500 \text{V DC}$

5. DIELECTRIC WITHSTANDING: 1000V AC CONTACT TO CONTACT

OR 1500VDC CONTACT TO SCREEN AND TEST PANEL

@0.5mA 50Hz OR 60Hz 1 MIN

6. DURABILITY: 750 CYCLES MIN
7. MATING/UNMATING FORCE: 30N/3.06KG MAX
8. RETENTION STRENGTH: 30N MIN FOR 60s ±5s
9. OPERATING TEMP: -40°C TO +85°C

10. STORAGE TEMP: -40°C TO +85°C RELATIVE HUMIDITY <80%

11. WAVE SOLDERING TEMP: 260±5°C FOR 5~10s

MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

٠.	THE WITH MICES LAND LESS CONTROLLED TO THE PROPERTY OF THE PRO					
			ACAD REFERENCE NO.: J6E Assembly			
	RJ45, SM	IT	DRAWN: Y.Z	DATE: 01.03/2020)	
			CHECKED:	DATE:		
	EDAC INC TORONTO, ONTARIO CANADA	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: 2:1	SHEET 1 OF	1	
			DRAWING NUMBER: J6E Assembly		ISSUE	
	YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: J6E01882	4L58110	1	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.