UNLESS O	TOLERANCE UNLESS OTHERWISE SPECIFIED			
.X	±0.25			
.XX	±0.13			
.XXX	±0.05			

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.




ISSUE NUMBER ORIGINAL




CURRENT RATING: 2A AC/DC **VOLTAGE RATING:** 100V AC/DC **TEMPERATURE RATING:** -40°C ~ 105°C **CONTACT RESISTANCE:** 10mΩ MAX. HOUSING RESISTANCE: 1000M Ω min. WITHSTANDING VOLTAGE: 800V AC / 60s

HOUSING MATERIAL: NYLON PA66, UL94V-0



140 Assembly

140-503-415-101



2.0 —	 	2.00)
)
0.70°		2.000	

8.0

闰

闰

回

6.1



SUGGESTED PCB LAYOUT



140 SERIES VERTICAL PCB MOUNT DRAWN: C.B DATE: March 27, 2020 CHECKED: DATE: THESE DRAWINGS AND SPECIFICATIONS OF 1 SCALE: 5:1 SHEET 1 ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED,OR COPIED 140 Assembly ISSUE DRAWING NUMBER: OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS

PART NUMBER:

WITHOUT WRITTEN PERMISSION.

ACAD REFERENCE NO.: