| 6.1 | | |
|---------------------|-------|----------------------|
| | 10 | 0.0 |
| 2.0 - | | -2.00 |
| ₀ 0.700/ | | 0 0 |
| | 2.000 | SUGGESTED PCB LAYOUT |

THIS SERIES FULLY CONFORMS TO

THE EUROPEAN UNION DIRECTIVES

2011/65/EU FOR RoHS COMPLIANCY.



THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.





ISSUE NUMBER ORIGINAL

NOTES:

CURRENT RATING: 2A AC/DC **VOLTAGE RATING:** 100V AC/DC -40°C ~ 105°C TEMPERATURE RATING: CONTACT RESISTANCE: 10mΩ MAX. WITHSTANDING VOLTAGE: 800V AC / 60s

HOUSING MATERIAL: NYLON PA66, UL94V-0





140 SERIES RIGHT ANGLE PCB MOUNT



EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

| ACAD REFERENCE NO.: 140 A | ssembly | | |
|--|----------------------|--|--|
| DRAWN: C.B | DATE: March 31, 2020 | | |
| CHECKED: | DATE: | | |
| SCALE: 1:0.5 | SHEET 1 OF 1 | | |
| DD 44/14 A 44/ | | | |

DRAWING NUMBER: 140 Assembly **ISSUE** PART NUMBER: 140-504-415-100