

TOLERANCE UNLESS OTHERWISE SPECIFIED	
.X	±0.25
.XX	±0.13
.XXX	±0.05


THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.




ISSUE NUMBER ORIGINAL







THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.




SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS PART NUMBER: WITHOUT WRITTEN PERMISSION.


ACAD REFERENCE NO.: 140 Assembly			
DRAWN: C.B	DATE: March 27, 2020		
CHECKED:	DATE:		
SCALE: 5:1	SHEET 1 OF 1		
DRAWING NUMBER: 140 Assembly			


140-505-415-101

NOTES: **CURRENT RATING:** 2A AC/DC **VOLTAGE RATING:** 100V AC/DC **TEMPERATURE RATING:** -40°C ~ 105°C **CONTACT RESISTANCE:** 10mΩ MAX. HOUSING RESISTANCE: 1000M Ω min. WITHSTANDING VOLTAGE: 800V AC / 60s

HOUSING MATERIAL: NYLON PA66, UL94V-0







TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE