




TOLERANCE UNLESS OTHERWISE SPECIFIED	
.X	$\pm 0.3$
.XX	$\pm 0.2$
.XXX	$\pm 0.1$

THIS IS A C.A.D. GENERATED DRAWING  
DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER  
ORIGINAL (1)



#### SPECIFICATIONS

VOLTAGE RATING:	250V AC/DC
CURRENT RATING:	3A AC/DC
WITHSTANDING VOLTAGE:	1000V AC/MIN
TEMPERATURE RANGE:	-40° C TO 105° C
INSULATION RESISTANCE:	1000MΩ MIN.
MATERIAL:	NYLON66, UL94V-0
COLOR:	NATURAL
USE CONTACT:	14K-292-452 (TIN-PLATED)
MATES WITH HOUSING:	14K-502-210-AA1
MATES WITH PIN HEADER:	14K-502-4XX-AA1
TOP ENTRY CONTACT CODES:	11,12,15
SIDE ENTRY CONTACT CODES:	16,21
MATES WITH SMT:	14K-502-4XXTAA1
SMT CONTACT CODES:	17,18

14K SERIES 2.50 PITCH SOCKET HOUSING	ACAD REFERENCE NO.: 14K Assembly		UNIT: MM
	DRAWN:	V.K.	DATE: 02/07/24
CHECKED: R.S.M		DATE: 02/21/24	
SCALE:	3:1	SHEET 1 OF 1	
DRAWING NUMBER:	14K-502-210-AA2	ISSUE	
PART NUMBER:	14K-502-210-AA2		1



THIS SERIES FULLY CONFORMS TO  
THE EUROPEAN UNION DIRECTIVES  
2011/65/EU FOR RoHS COMPLIANCE.



EDAC INC  
TORONTO, ONTARIO  
CANADA

YOUR CONNECTION TO QUALITY & SERVICE

THESE DRAWINGS AND SPECIFICATIONS  
ARE THE PROPERTY OF EDAC INC., AND  
SHALL NOT BE REPRODUCED, OR COPIED  
OR USED AS THE BASIS FOR THE  
MANUFACTURE OR SALE OF APPARATUS  
WITHOUT WRITTEN PERMISSION.