




TOLERANCE UNLESS OTHERWISE SPECIFIED	
.X	± 0.3
.XX	± 0.2
.XXX	± 0.1


THIS IS A C.A.D. GENERATED DRAWING
DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER	1
ORIGINAL	



RECOMMENDED PCB LAYOUT



SPECIFICATIONS:

VOLTAGE RATING: 250V AC/DC
CURRENT RATING: 3A AC/DC
WITHSTANDING VOLTAGE: 1000V AC/MIN
TEMPERATURE RANGE: -40 °C TO 105 °C
INSULATION RESISTANCE: $\geq 1000\text{M}\Omega$
CONTACT RESISTANCE: $\leq 10\text{m}\Omega$

INSULATOR MATERIAL: NYLON 66, UL94V-0
COLOR-NATURAL

CONTACT: BRASS, TIN PLATED

MATES WITH HOUSING: 14K-504-210-AA2

14K SERIES PIN HEADER, 2.50 PITCH, TOP ENTRY
THROUGH HOLE KINK 1

ACAD REFERENCE NO.: 14K Assembly UNIT: MM

DRAWN: V.K. DATE: 02/14/24

CHECKED: R.S.M. DATE: 02/21/24

SCALE: 2.5:1 SHEET 1 OF 1

DRAWING NUMBER: 14K-504-411-AA1 ISSUE

PART NUMBER: 14K-504-411-AA1 1



THIS SERIES FULLY CONFORMS TO
THE EUROPEAN UNION DIRECTIVES
2011/65/EU FOR RoHS COMPLIANCE.



EDAC INC
TORONTO, ONTARIO
CANADA

THESE DRAWINGS AND SPECIFICATIONS
ARE THE PROPERTY OF EDAC INC., AND
SHALL NOT BE REPRODUCED, OR COPIED
OR USED AS THE BASIS FOR THE
MANUFACTURE OR SALE OF APPARATUS
WITHOUT WRITTEN PERMISSION.