





TOLERANCE UNLESS OTHERWISE SPECIFIED	
.X	±0.3
.XX	±0.2
.XXX	±0.1

THIS IS A C.A.D. GENERATED DRAWING  
DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER	
ORIGINAL	①



RECOMMENDED PCB LAYOUT

SPECIFICATIONS	
VOLTAGE RATING:	250V AC/DC
CURRENT RATING:	3A AC/DC
WITHSTANDING VOLTAGE:	1000V AC/MIN
TEMPERATURE RANGE:	-40 °C TO 105 °C
INSULATION RESISTANCE:	≥ 1000 MΩ
CONTACT RESISTANCE:	≤ 10mΩ
INSULATOR MATERIAL:	LCP, UL94V-0
	COLOR - NATURAL
CONTACT:	BRASS, TIN PLATED
MATES WITH HOUSING:	14K-511-210-AA2
PACKAGING:	TAPE AND REEL



THIS SERIES FULLY CONFORMS TO  
THE EUROPEAN UNION DIRECTIVES  
2011/65/EU FOR RoHS COMPLIANCY.



EDAC INC  
TORONTO, ONTARIO  
CANADA  
YOUR CONNECTION TO QUALITY & SERVICE

THESE DRAWINGS AND SPECIFICATIONS  
ARE THE PROPERTY OF EDAC INC., AND  
SHALL NOT BE REPRODUCED, OR COPIED  
OR USED AS THE BASIS FOR THE  
MANUFACTURE OR SALE OF APPARATUS  
WITHOUT WRITTEN PERMISSION.

14K SERIES SMT, 2.50 PITCH, TOP ENTRY	ACAD REFERENCE NO.:	14K Assembly	UNIT: MM
	DRAWN:	V.K.	DATE: 02/16/24
	CHECKED:	R.S.M.	DATE: 02/21/24
	SCALE:	2.5:1	SHEET 1 OF 1
	DRAWING NUMBER:	14K-511-417TAA1	ISSUE 1
	PART NUMBER:	14K-511-417TAA1	