



THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.






ISSUE NUMBER








SECTION A-A



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



| MATERIAL: GLASS REINFORCED THERMOPLASTIC, PA66 CONTACT: COPPER ALLOY PLATING: 30µ" GOLD PLATING ON CONTACT AREA, TIN PLATING ON SOLDERING AREA | SPECIFICATIONS: | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|------------------------------|
| CONTACT: PLATING: COPPER ALLOY 30µ" GOLD PLATING ON CONTACT AREA, TIN PLATING ON | MATERIAL: | |
| PLATING: 30µ" GOLD PLATING ON CONTACT AREA, TIN PLATING ON | CONTACT | |
| AREA, TIN PLATING ON | | |
| · | PLATING: | |
| SOLDERING AREA | | |
| | | SOLDERING AREA |
| ELECTRICAL | ELECTRICAL | |
| VOLTAGE RATING: 250 VAC RMS | VOLTAGE RATING: | 250 VAC RMS |
| CURRENT RATING: 1A | CURRENT RATING: | 1A |
| DIELECTRIC | DIELECTRIC | |
| WITHSTANDING VOLTAGE: 500VAC RMS 60Hz FOR 60s | WITHSTANDING VOLTAGE | : 500VAC RMS 60Hz FOR 60s |
| INSULATION RESISTANCE: 1000 MEGA OHMS MIN AT 500VDC | INSULATION RESISTANCE: | 1000 MEGA OHMS MIN AT 500VDC |
| CONTACT RESISTANCE: 30 mOHMS MAX | CONTACT RESISTANCE: | 30 mOHMS MAX |
| MECHANICAL | MECHANICAL | |
| RETENTION FORCE: 460g MIN PER CONTACT | | 460a MIN PER CONTACT |
| INSERTION FORCE: 230g MAX PER CONTACT PAIR | | - |

ENVIRONMENTAL TEMPERATURE RANGE:

WITHDRAWAL FORCE:

-55°C TO +85°C

15g MIN PER CONTACT PAIR

| | ACAD REFERENCE NO.: 302 A | UNIT: MM | | |
|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------|----------------|-------|
| 302 SERIES CARD EDGE CONNECTOR | | DRAWN: J.L. | DATE: 06/06/23 | |
| | | CHECKED: R.S.M. | DATE: 04/09/24 | |
| EDAC INC | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND | SCALE: 1:1 | SHEET 1 OF | 2 |
| YOUR CONNECTION TO QUALITY & SERVICE | SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | DRAWING NUMBER: 302-020-65 | 56-201 | ISSUE |
| | | PART NUMBER: 302-020-65 | 6-201 | 2 |

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



| ISSUE NUMBER | |
|--------------|--|
| SEE PAGE 1 | |

| NO. OF POS. | CONTACT CODE 56 |
|-------------|-----------------|
| 04 | AVAILABLE |
| 06 | AVAILABLE |
| 08 | AVAILABLE |
| 10 | AVAILABLE |
| 12 | AVAILABLE |
| 14 | AVAILABLE |
| 16 | AVAILABLE |
| 20 | AVAILABLE |
| 22 | AVAILABLE |
| 24 | AVAILABLE |
| 26 | AVAILABLE |
| 30 | AVAILABLE |
| 32 | AVAILABLE |
| 36 | AVAILABLE |
| 40 | AVAILABLE |
| 48 | AVAILABLE |
| 50 | AVAILABLE |
| 52 | AVAILABLE |
| 60 | AVAILABLE |
| 68 | AVAILABLE |
| 70 | AVAILABLE |
| 80 | AVAILABLE |
| 100 | AVAILABLE |
| 110 | AVAILABLE |
| 120 | AVAILABLE |
| 124 | AVAILABLE |



| | | | ACAD REFERENCE NO.: 302 A | UNIT: MM | |
|--|--------------------------------------|------------------------------------------------------------------|---------------------------|----------------|-------|
| | 302 SERIES CARD EDGE CONNECTOR | | DRAWN: J.L. | DATE: 06/06/23 | |
| | | | CHECKED: R.S.M. | DATE: 04/09/24 | |
| | EDAC INC | OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS | SCALE: 3:2 | SHEET 2 OF | 2 |
| | YOUR CONNECTION TO QUALITY & SERVICE | | DRAWING NUMBER: 302-020-6 | 56-201 | ISSUE |
| | | | PART NUMBER: 302-020-6 | 56-201 | 2 |



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.