

TOLERANCE UNLESS OTHERWISE SPECIFIED

0-10 ±0.20

10-30 ±0.30

30-100 ±0.40

14.00

2.80 ±0.38

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER

ORIGINAL
REMOVE CODE 99

J.L. MAR.22/2024

SPECIFICATIONS:

MATERIAL: GLASS REINFORCED THERMOPLASTIC, PA66

CONTACT: COPPER ALLOY

PLATING: 15µ" GOLD PLATING ON CONTACT

AREA, TIN PLATING ON SOLDERING AREA

ELECTRICAL

VOLTAGE RATING: 250 VAC RMS

CURRENT RATING: 1A

DIELECTRIC

WITHSTANDING VOLTAGE: 500VAC RMS 60Hz FOR 60s

INSULATION RESISTANCE: 1000 MEGA OHMS MIN AT 500VDC

CONTACT RESISTANCE: 30 mOHMS MAX

**MECHANICAL** 

RETENTION FORCE: 460g MIN PER CONTACT

INSERTION FORCE: 230g MAX PER CONTACT PAIR WITHDRAWAL FORCE: 15g MIN PER CONTACT PAIR

**ENVIRONMENTAL** 

TEMPERATURE RANGE: -55°C TO +85°C

## ACAD REFERENCE NO. 302 Assembly UNIT: MM 302 SERIES CARD EDGE CONNECTOR DRAWN: J.L. DATE: 06/06/23 CHECKED: R.S.M. DATE: 04/09/24 THESE DRAWINGS AND SPECIFICATIONS SCALE: 2:1 1 2 SHEET EDAC INC ARE THE PROPERTY OF EDAC INC..AND TORONTO, ONTARIO SHALL NOT BE REPRODUCED, OR COPIED 302-030-358-201 DRAWING NUMBER: ISSUE OR USED AS THE BASIS FOR THE CANADA MANUFACTURE OR SALE OF APPARATUS YOUR CONNECTION TO QUALITY & SERVICE 2 WITHOUT WRITTEN PERMISSION. PART NUMBER: 302-030-358-201




ISSUE NUMBER SEE PAGE 1

THE IC A C.S. C.E. CENTER OF THE BIT WING	() [
DO NOT MAKE MANUAL REVISIONS TO MASTER.	Ă l

	DIMENSION A		
NO. OF POS.	CONTACT CODE 21	CONTACT CODE 58	
04	1.27		
06	2.54		
08	3.81		
10	5.08		
12	6.35		
14	7.62		
16	8.89		
20	11.43		
22 24	12.70		
24	13.97		
26	15.24		
30	17.78		
32	19.05		
36	21.59		
40	24.13		
48	29.21		
50	30.48		
52	31.75		
60	36.83		
68	41.91	NA	
70	43.18	NA	
80	49.53		
100	62.23	NA	
110	68.58	NA	
120	74.93	NA	
124	77.47	NA	

RECOMMENDED PCB LAYOUT (CONTACT CODE 21)



302-030-358-201 MOUNTING CODE **CONTACT CODE** 

NA = NOT AVAILABLE

