

TOLERANCE UNLESS OTHERWISE SPECIFIED

0-10 ±0.20 10-30 ±0.30 30-100 ±0.40

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER

ORIGINAL

REMOVE CODE 99 J.L. MAR.22/2024

SPECIFICATIONS:

MATERIAL: **GLASS REINFORCED** THERMOPLASTIC, PA66

CONTACT: **COPPER ALLOY**

30µ" GOLD PLATING ON CONTACT PLATING:

> AREA, TIN PLATING ON **SOLDERING AREA**

ELECTRICAL

VOLTAGE RATING: 250 VAC RMS

CURRENT RATING: 1A

DIELECTRIC

WITHSTANDING VOLTAGE: 500VAC RMS 60Hz FOR 60s

INSULATION RESISTANCE: 1000 MEGA OHMS MIN AT 500VDC

CONTACT RESISTANCE: 30 mOHMS MAX

MECHANICAL

RETENTION FORCE: 460g MIN PER CONTACT 230g MAX PER CONTACT PAIR **INSERTION FORCE:** WITHDRAWAL FORCE: 15g MIN PER CONTACT PAIR

ENVIRONMENTAL

TEMPERATURE RANGE: -55°C TO +85°C

302 SERIES CARD EDGE CONNECTOR

YOUR CONNECTION TO QUALITY & SERVICE

EDAC INC TORONTO, ONTARIO CANADA

3.50

6.20

2.54 7.62

> THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

ACAD REFERENCE NO.: 302 Assembly		UNIT: MIM
DRAWN: J.L.	DATE: 06/06/23	}
CHECKED: R.S.M.	DATE: 04/09/24	ļ
SCALE: 2:1	SHEET 1 O	F 2
DRAWING NUMBER: 302-040-621-201		ICCLIE

DRAWING NUMBER ISSUE 2 PART NUMBER: 302-040-621-201




ISSUE NUMBER SEE PAGE 1

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.	

	DIMENSION A		
NO. OF POS.	CONTACT CODE 21	CONTACT CODE 58	
04	1.27		
06	2.54		
08	3.81		
10	5.08		
12	6.35		
14 16	7.62		
16	8.89		
20	11.43		
22	12.70		
24	13.97		
26	15.24		
30	17.78		
32	19.05		
36	21.59		
40	24.13		
48	29.21		
50	30.48		
52	31.75		
60	36.83		
68	41.91	NA	
70	43.18	NA	
80	49.53		
100	62.23	NA	
110	68.58	NA	
120	74.93	NA	
124	77.47	NA	

RECOMMENDED PCB LAYOUT (CONTACT CODE 21)



302-040-621-201 MOUNTING CODE **CONTACT CODE**

NA = NOT AVAILABLE

