

TOLERANCE UNLESS OTHERWISE SPECIFIED

10-30 ±0.30

30-100 ±0.40

14.00

DO NOT MAKE MANUAL REVISIONS TO MASTER. 0-10 ±0.20

THIS IS A C.A.D. GENERATED DRAWING



ISSUE NUMBER

ORIGINAL

REMOVE CODE 99 J.L. MAR.22/2024

SPECIFICATIONS:

MATERIAL: **GLASS REINFORCED** THERMOPLASTIC, PA66

CONTACT: **COPPER ALLOY**

PLATING: 30µ" GOLD PLATING ON CONTACT

> AREA, TIN PLATING ON **SOLDERING AREA**

ELECTRICAL

VOLTAGE RATING: 250 VAC RMS

CURRENT RATING: 1A

DIELECTRIC

WITHSTANDING VOLTAGE: 500VAC RMS 60Hz FOR 60s

INSULATION RESISTANCE: 1000 MEGA OHMS MIN AT 500VDC

CONTACT RESISTANCE: 30 mOHMS MAX

MECHANICAL

RETENTION FORCE: 460g MIN PER CONTACT

230g MAX PER CONTACT PAIR **INSERTION FORCE:** WITHDRAWAL FORCE: 15g MIN PER CONTACT PAIR

ENVIRONMENTAL

TEMPERATURE RANGE: -55°C TO +85°C

302 SERIES CARD EDGE CONNECTOR

2.80 ±0.38



EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.


ACAD REFERENCE NO .: 302 Assembly UNIT: MM DRAWN: J.L. DATE: 06/06/23 CHECKED: R.S.M. DATE: 04/09/24 SCALE: 2:1 1 2 SHEET

302-040-658-201 DRAWING NUMBER: ISSUE 2 PART NUMBER: 302-040-658-201



ISSUE NUMBER
SEE PAGE 1

	DIMENSION A			
NO. OF POS.	CONTACT CODE 21	CONTACT CODE 58		
04	1.27			
06	2.54			
08	3.81			
10	5.08			
12	6.35			
14	7.62			
16	8.89			
20	11.43			
22	12.70			
24	13.97			
26	15.24			
30	17.78			
32	19.05			
36	21.59			
40	24.13			
48	29.21			
50	30.48			
52	31.75			
60	36.83			
68	41.91	NA		
70	43.18	NA		
80	49.53			
100	62.23	NA		
110	68.58	NA		
120	74.93	NA		
124	77.47	NA		



302-040-658-201

MOUNTING CODE

CONTACT CODE

NA = NOT AVAILABLE







ACAD REFERENCE NO.: 302 Assembly				UNIT: MM
DRAWN: J.L.	DATE:	06/06	5/23	
CHECKED: R.S.M.	DATE:	04/11	1/24	
SCALE: N.T.S	SHEET	2	OF	2
DRAWING NUMBER: 302-040-6	S58_201			ISSLIE

RAWING NUMBER:	302-040-658-201	ISSUE	
ART NUMBER:	302-040-658-201	2	