

TOLERANCE UNLESS OTHERWISE SPECIFIED

0-10 ±0.20 10-30 ±0.30 30-100 ±0.40

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER

ORIGINAL

REMOVE CODE 99 J.L. MAR.22/2024

SPECIFICATIONS:

MATERIAL: **GLASS REINFORCED** THERMOPLASTIC, PA66

CONTACT: **COPPER ALLOY**

15μ" GOLD PLATING ON CONTACT PLATING:

> AREA, TIN PLATING ON **SOLDERING AREA**

ELECTRICAL

VOLTAGE RATING: 250 VAC RMS

CURRENT RATING: 1A

DIELECTRIC

WITHSTANDING VOLTAGE: 500VAC RMS 60Hz FOR 60s

INSULATION RESISTANCE: 1000 MEGA OHMS MIN AT 500VDC

CONTACT RESISTANCE: 30 mOHMS MAX

MECHANICAL

460g MIN PER CONTACT **RETENTION FORCE:** 230g MAX PER CONTACT PAIR **INSERTION FORCE:** WITHDRAWAL FORCE: 15g MIN PER CONTACT PAIR

ENVIRONMENTAL

TEMPERATURE RANGE: -55°C TO +85°C

PART NUMBER:

302 SERIES CARD EDGE CONNECTOR

YOUR CONNECTION TO QUALITY & SERVICE

EDAC INC TORONTO, ONTARIO CANADA

3.50

6.20

2.54 7.62

> THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

ACAD REFERENCE NO.: 302 Assembly				UNIT: MIM
DRAWN: J.L.	DATE:	06/0	6/23	
CHECKED: R.S.M.	DATE:	04/09	9/24	
SCALE: 2:1	SHEET	1	OF	2
DRAWING NUMBER: 302-048-321-201		ISSUE		

302-048-321-201


2




ISSUE NUMBER SEE PAGE 1

A	

	DIMENSION A			
NO. OF POS.	CONTACT CODE 21	CONTACT CODE 58		
04	1.27			
06	2.54			
08	3.81			
10	5.08			
12	6.35			
14	7.62			
16	8.89			
20	11.43			
22	12.70			
24	13.97			
26	15.24			
30	17.78			
32	19.05			
36	21.59			
40	24.13			
48	29.21			
50	30.48			
52	31.75			
60	36.83			
68	41.91	NA		
70	43.18	NA		
80	49.53			
100	62.23	NA		
110	68.58	NA		
120	74.93	NA		
124	77.47	NA		







302-048-321-201 MOUNTING CODE **CONTACT CODE**

NA = NOT AVAILABLE







302-048-321-201

PART NUMBER: