

TOLERANCE UNLESS OTHERWISE SPECIFIED

30-100 ±0.40

14.00

DO NOT MAKE MANUAL REVISIONS TO MASTER. 0-10 ±0.20 10-30 ±0.30

THIS IS A C.A.D. GENERATED DRAWING



ISSUE NUMBER **ORIGINAL**

REMOVE CODE 99

J.L. MAR.22/2024

SPECIFICATIONS:

MATERIAL: **GLASS REINFORCED** THERMOPLASTIC, PA66

CONTACT: **COPPER ALLOY**

GOLD FLASH PLATING ON PLATING:

CONTACT AREA, TIN PLATING ON

SOLDERING AREA

ELECTRICAL

VOLTAGE RATING: 250 VAC RMS

CURRENT RATING: 1A

DIELECTRIC

WITHSTANDING VOLTAGE: 500VAC RMS 60Hz FOR 60s

INSULATION RESISTANCE: 1000 MEGA OHMS MIN AT 500VDC

CONTACT RESISTANCE: 30 mOHMS MAX

MECHANICAL

RETENTION FORCE: 460g MIN PER CONTACT

230g MAX PER CONTACT PAIR **INSERTION FORCE:** WITHDRAWAL FORCE: 15g MIN PER CONTACT PAIR

ENVIRONMENTAL

TEMPERATURE RANGE: -55°C TO +85°C

302 SERIES CARD EDGE CONNECTOR

2.80 ±0.38



EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

ACAD REFERENCE NO.: 302 As	ssembly	UNIT: MM
DRAWN: J.L.	DATE: 06/06/23	
CHECKED: R.S.M.	DATE: 04/09/24	
SCALE: 2:1	SHEET 1 OF	2
DDAMING NUMBER 202 050 259 201		ICCLIE

DRAWING NUMBER: 302-050-258-201 ISSUE 2 PART NUMBER: 302-050-258-201



ISSUE NUMBER SEE PAGE 1

UNIT: MM


2

ISSUE

O	\Box
/- \	
/ 1/	
	- -

	DIMENSION A		
NO. OF POS.	CONTACT CODE 21	CONTACT CODE 58	
04	1.27		
06	2.54		
08	3.81		
10	5.08		
12	6.35		
14	7.62		
	16 8.89		
20	11.43		
22	12.70		
24	13.97		
26	15.24		
30	17.78		
32			
36	21.59		
40	24.13		
48	29.21		
50	30.48		
52	31.75		
60	36.		
68	41.91	NA	
70	43.18	NA	
80	49.53		
100	62.23	NA	
110	68.58	NA	
120	74.93	NA	
124	77.47	NA	

RECOMMENDED PCB LAYOUT (CONTACT CODE 21)



ACAD REFERENCE NO.:

302 Assembly

302-050-258-201

302-050-258-201

DATE: 06/06/23

DATE: 04/11/24

SHEET 2 OF

302-050-258-201 MOUNTING CODE **CONTACT CODE**

NA = NOT AVAILABLE

