

TOLERANCE UNLESS OTHERWISE SPECIFIED

0-10 ±0.20 10-30 ±0.30 30-100 ±0.40

14.00

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER

ORIGINAL

REMOVE CODE 99 J.L. MAR.22/2024

SPECIFICATIONS:

MATERIAL: **GLASS REINFORCED** THERMOPLASTIC, PA66

CONTACT: **COPPER ALLOY**

30µ" GOLD PLATING ON CONTACT PLATING:

> AREA, TIN PLATING ON **SOLDERING AREA**

ELECTRICAL

VOLTAGE RATING: 250 VAC RMS

CURRENT RATING: 1A

DIELECTRIC

WITHSTANDING VOLTAGE: 500VAC RMS 60Hz FOR 60s

INSULATION RESISTANCE: 1000 MEGA OHMS MIN AT 500VDC

CONTACT RESISTANCE: 30 mOHMS MAX

MECHANICAL

RETENTION FORCE: 460g MIN PER CONTACT

230g MAX PER CONTACT PAIR **INSERTION FORCE:** WITHDRAWAL FORCE: 15g MIN PER CONTACT PAIR

ENVIRONMENTAL

TEMPERATURE RANGE: -55°C TO +85°C

302 SERIES CARD EDGE CONNECTOR

2.80 ±0.38

YOUR CONNECTION TO QUALITY & SERVICE

EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

ACAD REFERENCE NO.: 302 As	Assembly		UNIT: MM	
DRAWN: J.L.	DATE:	06/06	5/23	
CHECKED: R.S.M.	DATE:	04/09	9/24	
SCALE: 2:1	SHEET	1	OF	2
DD AVAILING NUMBER 202 050 659 201				100115

DRAWING NUMBER: 302-050-658-201 ISSUE 2 PART NUMBER: 302-050-658-201



ISSUE NUMBER SEE PAGE 1

UNIT: MM


2

ISSUE

Д	\Box

	DIMENSION A		
NO. OF POS.	CONTACT CODE 21	CONTACT CODE 58	
04	1.27		
06	2.54		
08	3.81		
10	5.08		
12	6.35		
14	7.62		
16	8.89		
20	11.43		
22	12.70		
24	13.97		
26	15.24		
30	17.78		
32	19.05		
36	21.59		
40	24.13		
48	29.21		
50	30.48		
52	31.75		
60		.83	
68	41.91	NA	
70	43.18	NA	
80	49.53		
100	62.23	NA	
110	68.58	NA	
120	74.93	NA	
124	77.47	NA	

RECOMMENDED PCB LAYOUT (CONTACT CODE 21)



302-050-658-201 MOUNTING CODE **CONTACT CODE**

ACAD REFERENCE NO.:

302 Assembly

DATE: 06/06/23

DATE: 04/11/24

SHEET 2 OF

NA = NOT AVAILABLE

