

TOLERANCE UNLESS OTHERWISE SPECIFIED

0-10 ±0.20 10-30 ±0.30 30-100 ±0.40

14.00

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER

ORIGINAL

REMOVE CODE 99 J.L. MAR.22/2024

SPECIFICATIONS:

MATERIAL: **GLASS REINFORCED** THERMOPLASTIC, PA66

CONTACT: **COPPER ALLOY**

GOLD FLASH PLATING ON PLATING:

CONTACT AREA, TIN PLATING ON

SOLDERING AREA

ELECTRICAL

VOLTAGE RATING: 250 VAC RMS

CURRENT RATING: 1A

DIELECTRIC

WITHSTANDING VOLTAGE: 500VAC RMS 60Hz FOR 60s

INSULATION RESISTANCE: 1000 MEGA OHMS MIN AT 500VDC

CONTACT RESISTANCE: 30 mOHMS MAX

MECHANICAL

RETENTION FORCE: 460g MIN PER CONTACT

230g MAX PER CONTACT PAIR **INSERTION FORCE:** WITHDRAWAL FORCE: 15g MIN PER CONTACT PAIR

ENVIRONMENTAL

TEMPERATURE RANGE: -55°C TO +85°C

302 SERIES CARD EDGE CONNECTOR

2.80 ±0.38



EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.


ACAD REFERENCE NO.: 302 As	2 Assembly		UNIT: MM	
DRAWN: J.L.	DATE:	06/06	6/23	
CHECKED: R.S.M.	DATE:	04/09	9/24	
SCALE: 2:1	SHEET	1	OF	2
DDAMING NUMBER 202 052 259 201				IOOUE


DRAWING NUMBER: 302-052-258-201 ISSUE 2 PART NUMBER: 302-052-258-201



ISSUE NUMBER
SEE PAGE 1

	DIAAFNICIONI A				
	DIMENSION A				
NO. OF POS.	CONTACT CODE 21	CONTACT CODE 58			
04	1.27				
06	2.54				
08	3.81				
10	5.08				
12	6.35				
14	7.62				
16	8.89				
20	11.43				
22	12.70				
24	13.97				
26	15.24				
30	17.78				
32	19.05				
36	21.59				
40	24.13				
48	29.21				
50	30.48				
52	31.75				
60	36.83				
68	41.91	NA			
70	43.18	NA			
80	49.53				
100	62.23	NA			
110	68.58	NA			
120	74.93	NA			
124	77.47	NA			





302-052-258-201

MOUNTING CODE

CONTACT CODE

NA = NOT AVAILABLE

