08	ounting Option -#4-40 Unified Threaded Inserts	Contact Detail 520-P.C. Tail .046x.013(1.17) .156 [3.96] Contact Spacing x	x0.33) - Tail LG.=.213(5.4 .140 [3.56] Row Spacing	11)	THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MA	STER.	ISSUE NUM ORIGINA	
	Card Slot Accepts — .054 (1.37) to .070 (1.78) Thick P.C. Board							
<u> </u>								
'	0.156[3.96]	5.468[138.89]] —	-				
		5.614[142.60] 5.900[149.86]		•	-			
						,	.38] Slot	
						,	0.330 [8.38] Card Slot	
	A							
1					<u> </u>	1		
+								
1.68] -	A J	6.210[157.73]]		_	0.125[3.18] S	ECTION	1 A-A
460[11.68]			Point		t of Contact ACAD REFERENCE N		IG MASTER	
Ö	See Accompanying Page for:		Part Number: 305-068-520-508		DRAWN: J.LEE CHECKED:	DATE: SEF		
			EDAC INC		THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIE	SCALE: NTS	SHEET 1	
	Mounting Options		TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE		SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER 305 Assembly	y	ISSUE 1

