Mounting Option 12128 (3:25) Dia. Side Mounting Holes 500-Wire Hole .087x.013 .156 [3.96] Contact Space		Contact Detail 500-Wire Hole .087x.013(2.21x .156 [3.96] Contact Spacing x .1	0.33) - Tail LG.=.282(7.16) 40 [3.56] Row Spacing		THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER		ISSUE NUM ORIGINA	
	Card Slot Accepts .054 (1.37) to .070 (1.78) Thick P.C. Board							
\(\frac{1}{4}\)	-0.156[3.96]	6.560 [166 6.706 [170 6.992 [177	0.62] ————————————————————————————————————					
						0 330 G 8 8	Card Slot	
[89]								SECTION A-A
0.460[11.68]		7.302[185	92[177.60]			0.125[3.18] Point of Contact		
						ACAD REFERENCE NO. 305 ENG MASTE DRAWN: J.LEE DATE: SEPT. 21/09		
Soo Accompanying Page for			EDAC INC		THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC. AND	CHECKED: SCALE: NTS	DATE: SHEET	1 OF 2
See Accompanying Page for: Mounting Options		YOU	TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE		SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER 305 Assembly	/	ISSUE 1

