

#### **Mounting Option**

04-.156 (3.96) Dia. Mounting Holes

#### **Contact Detail**

523-P.C. Tail .025 Sq.(0.64 Sq.) - Tail LG=.390(9.91) .156 [3.96] Contact Spacing x .200 [5.08] Row Spacing





## **See Accompanying Page for:**

- **Bend Detail**
- **Mounting Options**
- **Features and Specifications**



|                               | 0.388 [9.86]<br>Card Slot |
|-------------------------------|---------------------------|
| .160 [4.06] Point of Contact— |                           |
|                               |                           |
|                               | SECTION A-A               |

| Part Number: 333-006-523-60 |  |                                  |  |
|-----------------------------|--|----------------------------------|--|
| EDNG                        | EDAC INC<br>TORONTO, ONTARIO<br>CANADA | THES<br>ARE<br>SHAI<br>OR<br>MAN |  |

333 Series Card Edge Connector

YOUR CONNECTION TO QUALITY & SERVICE WITHOUT WRITTEN PERMISSION.

| SCALE: NTS     | SHEET | 1 OF 4 |
|----------------|-------|--------|
| DRAWING NUMBER |       | ISSUE  |
| 333 Assembly   |       | 1      |

ACAD REFERENCE NO. 333 ENG MASTER

DATE: OCT. 14/09

J.LEE

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.

1



| 333 Series Card Edge Connector<br>Contact Bend Detail |  | ACAD REFERENCE NO. 333 ENG MASTER |                  |        |  |
|---|--|-----------------------------------|------------------|--------|--|
|   |  | DRAWN: J.LEE                      | DATE: OCT. 14/09 |        |  |
|   |  | CHECKED:                          | DATE:            |        |  |
| EDAC INC THESE DRAWINGS AND SPECIFICATIONS            |  | SCALE: NTS                        | SHEET :          | 2 OF 4 |  |
| TORONTO, ONTARIO                                      | ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE | DRAWING NUMBER                    |                  | ISSUE  |  |
| YOUR CONNECTION TO QUALITY & SERVICE                  | MANUFACTURE OR SALE OF APPARATUS   | 333 Assembly                      |                  | 1      |  |

THIS IS A C.A.D. GENERATED DRAWING
DO NOT MAKE MANUAL REVISIONS TO MASTER



1220F NOWRE

DRIGINAL

1



| 333 Series Card Edge Connector |  | ACAD REFERENCE NO. 333 ENG MASTER  |          |             |           |        |
|--------------------------------|--|--|----------|-------------|-----------|--------|
|                                |  | DRAWN:   | J.LEE    | DATE: O     | CT. 14/09 |        |
|                                | Mounting Options                           |  | CHECKED: |             | DATE:     |        |
|                                | EDAC INC THESE DRAWINGS AND SPECIFICATIONS |  | SCALE:   | NTS         | SHEET ;   | 3 OF 4 |
|                                | TORONTO, ONTARIO                           | ARE THE PROPERTY OF EDAC INC.,AND<br>SHALL NOT BE REPRODUCED,OR COPIED<br>OR USED AS THE BASIS FOR THE | DRAWING  | NUMBER      |           | ISSUE  |
|                                | YOUR CONNECTION TO QUALITY & SERVICE       | MANUFACTURE OR SALE OF APPARATUS   | 3        | 33 Assembly |           | 1      |

ISSUE NUMBER

ORIGINAL



### **Features**

- .156 (3.96) Contact Spacing x .200 (5.08) Row Spacing
- Accepts .062 (1.57) Nominal Thickness P.C. Board
- High Profile Insulator Body .600 (15.24)
- Contact Termination Options include P.C. Tail, Wire Hole, Wire Wrap, 90 Degree, & Extender Board Bends
- Single or Dual Row Configurations
- Variety of Mounting Options, Flush or Offset Lugs
- Accepts Between Contact and In-Contact Polarizing Keys

# **Specifications**

- Insulator Material: Thermoplastic Polyester, UL 94V-0, Colour: Green
- Contact Material: Copper, Nickel, Tin Alloy CA-725
- Contact Plating: Gold on the Mating Area, Tin on the Contact Tails, Nickel Underplate
- Current Rating: 3 Amperes Continuous
- Contact Resistance: 10 Milliohms Maximum
- Dielectric Withstanding Voltage: 1800 V AC rms at Sea Level Between Adjacent Contacts
- Insulation Resistance: 5000 Megohms Minimum
- Operating Temperature: -65 to +105 Degrees C
- Insertion Force: 16 oz (4.45 N) Maximum per Contact Pair when Tested with a .070 (1.78) Thick Gauge
- Withdrawal Force: 1 oz (0.28 N) Minimum per Contact Pair when Tested with a .054 (1.37) Thick Gauge

| 333 Series Card Edge Connector                           | ACAD REFERENCE NO. 333 ENG MASTER      |
|--|--|
| Features and Specifications                              | DRAWN: J.LEE DATE: OCT. 14/09          |
| redictes and specifications                              | CHECKED: DATE:                         |
| EDAC INC THESE DRAWINGS AND ARE THE PROPERTY OF          |  |
| IORONIO, ONIARIO SHALL NOT BE REPRO                      | DDUCED, OR COPIED DRAWING NUMBER ISSUE |
| YOUR CONNECTION TO QUALITY & SERVICE WITHOUT WRITTEN PER | LE OF APPARATUS 333 Accombly 1         |