



### Specifications:

- Current Rating: 2 Amperes @ 20°C
- Contact Material: Brass
- Contact Plating: Selective Gold Plating
- Contact Resistance: 30 milliohms, maximum
- Insulator Material: 30% Glass Filled PBT, UL 94V-0
- Insulation Resistance: Mated - 1000 Mega ( $10^6$ ) ohms
- Dielectric Withstanding Voltage: 1000 V.A.C RMS
- Basic Grid: 2.54mm (.100")
- Operating Temperature: -55°C to +105°C



THIS SERIES FULLY CONFORMS TO THE  
EUROPEAN UNION DIRECTIVES 2002/95/EC  
AND 2002/96/EC FOR RoHS COMPLIANCY

461 Series Metal-To-Metal Plug DIN Connector  
PART NUMBER: 461-132-681-111



EDAC INC  
TORONTO, ONTARIO  
CANADA

YOUR CONNECTION TO QUALITY & SERVICE

THESE DRAWINGS AND SPECIFICATIONS  
ARE THE PROPERTY OF EDAC INC., AND  
SHALL NOT BE REPRODUCED, OR COPIED  
OR USED AS THE BASIS FOR THE  
MANUFACTURE OR SALE OF APPARATUS  
WITHOUT WRITTEN PERMISSION

ACAD REFERENCE NO.	461 -ENG-MASTER
--------------------	-----------------

DRAWN: R. STA. MONICA	DATE: JUL.20/10
-----------------------	-----------------

CHECKED:	DATE:
----------	-------

SCALE:	NTS	SHEET 1 OF 1
--------	-----	--------------

DRAWING NUMBER	ISSUE
461 -ENG-MASTER	1