ISSUE NUMBER THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER. ORIGINAL 1 MATERIALS: HOUSING: PBT, UL94V-0 1. 2. WIRE-HOUSING SEAL: SILICON RUBBER SPECIFICATIONS: S 0.6] 1. PITCH: 2.0MM 2. 3. RATED VOLTAGE: 250V RATED CURRENT: 2A MAX 4. WITHSTAND VOLTAGE: AC1000V R.M.S. 5. CONTACT RESISTANCE: 10 mOHMS MAX INSULATION RESISTANCE: 6. 1000 MOHMS MIN/DC 500V 7. TEMPERATURE RANGE: -40°C ~ +105°C 8. WATERPROOF GRADE: TESTED AND **CERTIFIED TO IP67** 0.4 11.3 0.3] 65 2 INSIDE ITEM NO. QTY. DESCRIPTION 566-004-000-811_Housing 1 1 2 566-004-000-811 Rubber 1 ACAD REFERENCE NO. 566 ASSEMBLY 566 SERIES 4 SOCKET WATERPROOF CONNECTOR DRAWN:R.STA.MONICA DATE: NOV.02/10

CHECKED:

THESE DRAWINGS AND SPECIFICATIONS

SHALL NOT BE REPRODUCED, OR COPIED

MANUFACTURE OR SALE OF APPARATUS

ARE THE PROPERTY OF EDAC INC., AND

OR USED AS THE BASIS FOR THE

WITHOUT WRITTEN PERMISSION.

SCALE: NOT TO SCALE

566-004-000-811

DRAWING NUMBER

DATE:

SHEET 1 OF 1

ISSUE

1

EUROPEAN UNION DIRECTIVES 2002/95/EC AND 2002/96/EC FOR RoHS COMPLIANCY

THIS SERIES FULLY CONFORMS TO THE

FOR RoHS COMPLIANCY

YOUR CONNECTION TO QUALITY & SERVICE

EDAC INC

TORONTO, ONTARIO