
|             |            |      | <u> </u> | 30. | 80 ±  | 0.38           | <b>→</b> |
|-------------|------------|------|----------|-----|-------|----------------|----------|
| 12.60 ±0.38 | 8.36 ±0.25 | 4    |          |     | 99 ±  |                | 1        |
| 12.6        | 8.36       | 2.84 |          |     | 16.92 |                |          |
|             |            | -    | (1)      | (:  | • • • | $\mathfrak{I}$ | <b>D</b> |
| L           |            |      | _        |     |       | 2.77           |          |
|             |            |      | _<br>10° |     |       | 1.38           | <u>5</u> |







THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ORIGINAL 1





## NOTES:

MATERIAL:

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0

SHELL: STEEL, TIN PLATED

CONTACT: COPPER ALLOY,  $15\mu$  GOLD PLATED

OPERATING TEMPERATURE: -55°C to +105°C

CURRENT RATING: 3A PER CONTACT CONTACT RESISTANCE:  $25 m\Omega$  MAX. INSULATOR RESISTANCE:  $5000 M\Omega$  min.

**DIELECTRIC** 

WITHSTANDING VOLTAGE: 1000V AC rms

PART NUMBER:

## THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

627 SERIES D-SUB CONNECTOR

| SW REFERENCE NO.: 627 A   | SSEMBLY            |
|---------------------------|--------------------|
| DRAWN: C.B                | DATE: AUG. 01/2018 |
| CHECKED:                  | DATE:              |
| SCALE: 1:1                | SHEET 1 OF 1       |
| DRAWING NUMBER: 627-009-3 | 381-276 ISSUE      |

627-009-381-276