





11.0 6.1 5.30 ±0.30



NOTES:

MATERIAL: HOUSING: SHELL:

CONTACT:

PA6T THERMOPLASTIC, WHITE, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ" GOLD PLATED

OPERATING TEMPERATURE: -55°C ~ 125°C

CURRENT RATING: 5A PER CONTACT CONTACT RESISTANCE: 10mΩ MAX. **INSULATOR RESISTANCE:** 5000MΩ min. DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC min.

CONNECTOR		SW REFERENCE NO.: 627 ASSEMBLY				
		DRAWN: C.B		DATE: AUG. 01/2018		
		CHECKED:		DATE:		
	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: 1:1		SHEET 1 OF 1		
		DRAWING NUMBER: 627-M15-622-W		-622-WN1		ISSUE
		PART NUMBER:	627-M15	627-M15-622-WN1		1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



627 SERIES D-SUB

EDAC INC TORONTO, ONTARIO CANADA

SW REFERENCE NO.: 627 A	SSEMBLY		
DRAWN: C.B	DATE: AUG. 01/2018		
CHECKED:	DATE:		
SCALE: 1:1	SHEET 1 OF 1		
DRAWING NUMBER: 627-M15-	622-WN1 ISSUE		
PART NUMBER: 627-M15-	622-WN1 1		

(1)