

CURRENT RATING: 5A PER CONTACT CONTACT RESISTANCE: $25m\Omega$ MAX. INSULATOR RESISTANCE: 5000MΩ min. DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC rms

627 SERIES D-SUB CONNECTOR		SW REFERENCE NO.: 627 ASSEMBLY			
		DRAWN: C.B	DATE: AUG. 01/2	DATE: AUG. 01/2018	
		CHECKED:	DATE:		
EDAC INC TORONTO, ONTARIO CANADA ECTION TO QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: 1:1	SHEET 1 OF	1	
		DRAWING NUMBER: 627-M2	25-623-GN3	ISSUE	
		PART NUMBER: 627-M2	25-623-GN3	1	



COMPLIANT

0.80

12.50

8.30

N

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

