TOLERANCE
 THIS IS A C.A.D. GENERATED DRAWING


 UNLESS OTHERWISE SPECIFIED
 DO NOT MAKE MANUAL REVISIONS TO MASTER.


 .X
 ±0.25




ISSUE NUMBER
ORIGINAL

(1)







NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

OPERATING TEMPERATURE:

.XX ±0.13 .XXX ±0.05

POWER/CO-AX CONTACT RATING:40A (CURRENT)(IF PRESENT)SIGNAL CONTACT CURRENT RATING:5A PER CONTACTSIGNAL CONTACT RESISTANCE:10mΩ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 5000MΩ min.


1000V AC rms

-55°C ~ 125°C

THERMOPLASTIC POLYESTER, UL94V-0

COPPER ALLOY, GOLD FLASH PLATED

STEEL, NICKEL PLATED



					SW REFERENCE NO.: 629 COMBO ASSEMBLY				
	COMBINATION D-SUB			DRAWN: C.B		DATE: JAN. 01/2019			
					DATE:				
	EDAC INC TORONTO, ONTARIO CANADA	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1	:1)	SHEET 1	OF	2		
			DRAWING NUMBER:	1240-4N6		ISSUE			
YOUR CONNECTION TO	QUALITY & SERVICE		PART NUMBER:	629-11W	1240-4N6		1		



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

