

TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.









NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATED

OPERATING TEMPERATURE:

 .X
 ±0.25

 .XX
 ±0.13

 .XXX
 ±0.05

POWER/CO-AX CONTACT RATING:10A (CURRENT)(IF PRESENT)SIGNAL CONTACT CURRENT RATING:5A PER CONTACTSIGNAL CONTACT RESISTANCE:10mΩ MAX.INSULATOR RESISTANCE:5000MΩ min.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:

	COMBINATION D-SUB			SW REFERENCE NO.: 629 COMBO ASSEMBLY			
				DRAWN: C.B		DATE: JAN. 01/2019	
			CHECKED:		DATE:		
	EDACI	EDAC INC TORONTO, ONTARIO CANADA DNNECTION TO QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1	:1)	SHEET 1 OF	2
				DRAWING NUMBER: 629-11W125		1250-1N2	ISSUE
	YOUR CONNECTION TO QUALITY & SE			PART NUMBER:	629-11W	1250-1N2	1

-55°C ~ 125°C

1000V AC rms

