

TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.

6.10









 .X
 ±0.25

 .XX
 ±0.13

 .XXX
 ±0.05

NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

**OPERATING TEMPERATURE:** 

POWER/CO-AX CONTACT RATING:30A (CURRENT)(IF PRESENT)SIGNAL CONTACT CURRENT RATING:5A PER CONTACTSIGNAL CONTACT RESISTANCE:10mΩ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 5000MΩ min.

1000V AC rms

|     | COMBINATION D-SUB                    |   | SW REFERENCE NO.: 629 COMBO ASSEMBLY |                   |       |
|-----|--------------------------------------|---|--------------------------------------|-------------------|-------|
|     |                                      |   | DRAWN: C.B                           | DATE: JAN. 01/201 | 19    |
|     |                                      |   | CHECKED:                             | DATE:             |       |
|     | EDAC INC                             | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND  | SCALE: (IN C.A.D. 1:1)               | SHEET 1 OF        | 2     |
| YOL | TORONTO, ONTARIO<br>CANADA           | SHALL NOT BE REPRODUCED, OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | DRAWING NUMBER: 629-11W1250-3T6      |                   | ISSUE |
|     | YOUR CONNECTION TO QUALITY & SERVICE |   | PART NUMBER: 629-11W                 | 1250-3T6          | 1     |



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY. -55°C ~ 125°C 30A (CURRENT)

STEEL, TIN PLATED



THERMOPLASTIC POLYESTER, UL94V-0

COPPER ALLOY, GOLD FLASH PLATED

