

THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.



| ISS | UE NUMBER |
|----------|-----------|
| ORIGINAL | |

(1)





NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

(IF PRESENT)

OPERATING TEMPERATURE:

.X ±0.25 .XX ±0.13 .XXX ±0.05


POWER/CO-AX CONTACT RATING:

SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:


INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 30A (CURRENT) $10m\Omega$ MAX.

5000MΩ min.

1000V AC rms



| | COMBINATION D-SUB | | SW REFERENCE NO.: 629 COMBO ASSEMBLY | | | |
|--------------------|--|---|--------------------------------------|-----------|--------------------|-------|
| | | | DRAWN: C.B | | DATE: JAN. 01/2019 | |
| | | | CHECKED: | | DATE: | |
| EDAC INC | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC. AND | SCALE: (IN C.A.D. 1:1 |) | SHEET 1 O | F 2 | |
| | YOUR CONNECTION TO QUALITY & SERVICE | SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | DRAWING NUMBER: 629-11W ² | | 1650-3T3 | ISSUE |
| YOUR CONNECTION TO | | | PART NUMBER: | 629-11W1 | 1650-3T3 | 1 |



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY. COMPLIANT

-55°C ~ 125°C

STEEL, TIN PLATED



THERMOPLASTIC POLYESTER, UL94V-0

