


NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED
OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	30A (CURRENT)
SIGNAL CONTACT CURRENT RATING:	5A PER CONTACT 10mΩ MAX.
INSULATOR RESISTANCE:	5000MΩ min.
DIELECTRIC	

				SW REFERENCE NO.: 630 COMBO ASSEMBLY				
COMBINATION D-SUB		DRAWN: C.B		DATE: JAN. 01/2019		19		
			CHECKED:		DATE:			
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: (IN C.A.D. 1	l:1)	SHEET 1	OF	2		
	TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE	DRAWING NUMBER: 630-11W		/1240-3T5		ISSUE	
YOUR CONNECTION TO QUALITY	YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-11W124		240-3T5		1	



.XX ±0.13

.XXX ±0.05

10.70

5.80

INSU DIEL WITHSTANDING VOLTAGE:

1000V AC rms

S COMPLIANT

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

