





1











NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ GOLD PLATED
OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	10A (CURRENT)
SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.
INSULATOR RESISTANCE:	5000MΩ min.
DIELECTRIC WITHSTANDING VOLTAGE:	1000V AC rms

			SW REFERENCE NO.: 630 COMBO ASSEMBLY				
COMBINATION D-SUB		DRAWN: C.B	DATE: JAN. 01/2019				
		CHECKED:	DATE:				
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2			
YOUR CONNECTION TO QUALITY & SERVICE		DRAWING NUMBER: 630-11W	1640-1NE	ISSUE			
		PART NUMBER: 630-11W	1640-1NE	1			



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

E		A	G	EDAC TORONTO, CANA
YOUF	R COI	NNEC	TION TO	QUALITY & S

SW REFERENCE NO.: 630 C			COMBO ASSEMBLY				
DRAWN: C.B			DATE: JAN. 01/2019				
CHECKED:			DATE:				
SCALE:	(IN C.A.D. 1:1)		SHEET	1	OF	2	
							1

