


.XX ±0.13


.XXX ±0.05


10.70

5.80










NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ GOLD PLATED
OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	40A (CURRENT)
SIGNAL CONTACT CURRENT RATING:	5A PER CONTACT
SIGNAL CONTACT RESISTANCE:	10mΩ MAX.
INSULATOR RESISTANCE:	5000MΩ min.
DIELECTRIC	
WITHSTANDING VOLTAGE:	1000V AC rms



			SW REFERENCE NO.: 630 COMBO ASSEMBLY			
COMBINATION D-SUB		DRAWN: C.B	DATE: JAN. 01/2019			
		CHECKED:	DATE:			
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2		
CANADA	OR USED AS THE BASIS FOR THE	DRAWING NUMBER: 630-11W	1640-4ND	ISSUE		
YOUR CONNECTION TO QUALITY & SERVIC	E MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	PART NUMBER: 630-11W	1640-4ND	1		



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

SW REFERENCE NO.:	630 C	OWBO AS	SSEIMI	BLY	
DRAWN: C.B		DATE:	JAN.	01/20	19
CHECKED:	DATE:				
SCALE: (IN C.A.D. 1:1)		SHEET	1	OF	2
DRAWING NUMBER:	1640-4N	D		ISSUE	
PART NUMBER: 630-11W		1640-4N	D		1

