


.XX ±0.13

.XXX ±0.05

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V STEEL, TIN PLATED COPPER ALLOY, 30µ GOLD PLATED	/-0
OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT)	30A (CURRENT)	₩~
SIGNAL CONTACT CURRENT RATING:	5A PER CONTACT	\mathbf{s}
SIGNAL CONTACT RESISTANCE:	10mΩ MAX.	\mathbb{Z}
INSULATOR RESISTANCE: DIELECTRIC	5000MΩ min.	Ľ
	40001/ 40	
WITHSTANDING VOLTAGE:	1000V AC rms	

	SW REFERENCE NO.: 630 COMBO ASSEMBLY			
COMBINATION D-SUB		DRAWN: C.B	DATE: JAN. 01/20	19
			DATE:	
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
EDEC TORONTO, ONTARIO CANADA		DRAWING NUMBER: 630-11W1650-3T2 I		ISSUE
YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-11W	1650-3T2	1



THIS SERIES FULLY CONFORMS TO

THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

J

COMPLIANT

