



(1)





## NOTES:

MATERIAL:HOUSING:THERMOPLASTIC POLYESTER, UL94V-0SHELL:STEEL, TIN PLATEDCONTACT:COPPER ALLOY, GOLD FLASH PLATEDOPERATING TEMPERATURE:-55°C ~ 125°C


POWER/CO-AX CONTACT RATING:20A (CURRENT)(IF PRESENT)SIGNAL CONTACT CURRENT RATING:5A PER CONTACTSIGNAL CONTACT RESISTANCE:10mΩ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:


.XX ±0.13

.XXX ±0.05

10mΩ MAX. 5000MΩ min. 1000V AC rms



| COMBINATION D-SUB  |  | SW REFERENCE NO.: 630 COMBO ASSEMBLY |                  |       |
|--|--|--------------------------------------|------------------|-------|
|  |  | DRAWN: C.B                           | DATE: JAN. 01/20 | 19    |
|  |  | CHECKED:                             | DATE:            |       |
| EDAG INC<br>TORONTO, ONTARIO<br>CANADA<br>YOUR CONNECTION TO QUALITY & SERVICE | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND<br>SHALL NOT BE REPRODUCED,OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1)               | SHEET 1 OF       | 2     |
|  |  | DRAWING NUMBER: 630-13W3240-2TD      |                  | ISSUE |
|  |  | PART NUMBER: 630-13W                 | 3240-2TD         | 1     |





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

