


NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC STEEL, TIN PLATE COPPER ALLOY, G		
OPERATING TEMPERATURE:	-55°C ~ 125°C		
POWER/CO-AX CONTACT RATING:	20A (CURRENT)		

(IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:



COMBINATION D-SUB		SW REFERENCE NO.: 630 COMBO ASSEMBLY			
		DRAWN: C.B	DATE: JAN. 01/2019		
		CHECKED:	DATE:		
EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE		SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
	DRAWING NUMBER: 630-3W3-240-2T1		ISSUE		
		PART NUMBER: 630-3W3	-240-2T1	1	



COMPLIANT

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

POLYESTER, UL94V-0 ED GOLD FLASH PLATED

.XX ±0.13

.XXX ±0.05

10.70

5.80

10mΩ MAX.

5000MΩ min.

1000V AC rms

