






TOLERANCE UNLESS OTHERWISE SPECIFIED	
.X	±0.30
.XX	±0.20
.XXX	±0.10
.XXXX	±0.05

THIS IS A C.A.D. GENERATED DRAWING  
DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER	
ORIGINAL	①



RECOMMENDED P.C.B HOLE LAYOUT  
TOP VIEW

**NOTE:**  
**ELECTRICAL SPECIFICATIONS:**  
**VOLTAGE RATING:** 30V MAX.  
**CURRENT RATING:** 1.5A  
**CONTACT RESISTANCE:** 30mΩ MAX.  
**INSULATOR RESISTANCE:** 1000MΩ min.  
**DIELECTRIC WITHSTANDING VOLTAGE:** 500V AC  
**OPERATING TEMPERATURE:** -40°C ~ 85°C

**MATERIAL & FINISH:**  
**SHELL:** COPPER ALLOY, NICKEL PLATED  
**HOUSING:** PBT, WHITE IN COLOUR, UL94V-0  
**CONTACTS:** COPPER ALLOY, 30µ" GOLD PLATED



THIS SERIES FULLY CONFORMS TO  
THE EUROPEAN UNION DIRECTIVES  
2011/65/EU FOR RoHS COMPLIANCY.



YOUR CONNECTION TO QUALITY & SERVICE

EDAC INC  
TORONTO, ONTARIO  
CANADA

THESE DRAWINGS AND SPECIFICATIONS  
ARE THE PROPERTY OF EDAC INC., AND  
SHALL NOT BE REPRODUCED, OR COPIED  
OR USED AS THE BASIS FOR THE  
MANUFACTURE OR SALE OF APPARATUS  
WITHOUT WRITTEN PERMISSION.

690 SERIES RECEPTACLES USB TYPE-A RIGHT ANGLE PCB		ACAD REFERENCE NO.: 690C304-X34-02X	
DRAWN: C.B		DATE: February 12, 2021	
CHECKED:		DATE:	
SCALE: 2:1		SHEET 1 OF 1	
DRAWING NUMBER: 690C304-X34-02X			ISSUE
PART NUMBER: 690C304-634-020			1