






TOLERANCE UNLESS OTHERWISE SPECIFIED	
.X	±0.25
.XX	±0.13
.XXX	±0.05

THIS IS A C.A.D. GENERATED DRAWING
DO NOT MAKE MANUAL REVISIONS TO MASTER.




ISSUE NUMBER	
ORIGINAL	①



NOTES:

MATERIAL	BRASS, T=0.30m
SHELL:	NICKEL/TIN PLATED
SHELL PLATING:	PHOSPHOR BRONZE T=0.25
TERMINAL:	6μ" GOLD PLATED
TERMINAL PLATING:	
HOUSING:	PBT, UL94V-0, WHITE
ELECTRICAL:	
RATED VOLTAGE:	30V
RATED CURRENT:	1.5AMP AT 250V AC
INSULATION RESISTANCE:	1000MΩ MIN
CONTACT RESISTANCE:	30mΩ MAX.
DIELECTRIC WITHSTANDING VOLTAGE:	500V AC
ENVIRONMENTAL	
TEMPERATURE RANGE:	-40°C TO +85°C
MECHANICAL:	
INSERTION FORCE:	35N MAX.
EXTRACTION FORCE:	10N



RECOMMENDED P.C.B HOLE LAYOUT
TOP VIEW (TOLERANCE: ±0.10)

690 SERIES SHORT BODY USB TYPE-A
RECEPTACLE VERTICAL PCB

ACAD REFERENCE NO.: 690E104-34C-420	
DRAWN: P.M	DATE: DEC 18/2020
CHECKED: C.B	DATE: DEC 18/2020
SCALE: 2:1	SHEET 1 OF 1
DRAWING NUMBER: 690E104-34C-420	ISSUE
PART NUMBER: 690E104-34C-420	1



THIS SERIES FULLY CONFORMS TO
THE EUROPEAN UNION DIRECTIVES
2011/65/EU FOR RoHS COMPLIANCY.



YOUR CONNECTION TO QUALITY & SERVICE

EDAC INC
TORONTO, ONTARIO
CANADA

THESE DRAWINGS AND SPECIFICATIONS
ARE THE PROPERTY OF EDAC INC., AND
SHALL NOT BE REPRODUCED, OR COPIED
OR USED AS THE BASIS FOR THE
MANUFACTURE OR SALE OF APPARATUS
WITHOUT WRITTEN PERMISSION.