







THIS IS A C.A.D. GENERATED DRAWING  
DO NOT MAKE MANUAL REVISIONS TO MASTER.



TOLERANCE UNLESS OTHERWISE SPECIFIED	
.X	±0.25
.XX	±0.13
.XXX	±0.05



**NOTE:**  
**ELECTRICAL SPECIFICATIONS:**  
 VOLTAGE RATING: 30V MAX.  
 CURRENT RATING: 1.8A  
 CONTACT RESISTANCE: 30mΩ MAX.  
 INSULATOR RESISTANCE: 100MΩ min.  
 DIELECTRIC WITHSTANDING VOLTAGE: 100V AC  
 OPERATING TEMPERATURE: -25°C ~ 85°C

**MATERIAL & FINISH:**  
 JACKET: STAINLESS STEEL, T=0.30, NICKEL PLATING  
 SHELL: COPPER ALLOY, T=0.30, NICKEL PLATING  
 HOUSING: PBT, BLACK IN COLOUR, UL94V-0  
 CONTACTS: COPPER ALLOY, T=0.20, 3μ" GOLD PLATING

<b>690 SERIES RECEPTACLES USB 3.0 TYPE-A CABLE END SOLDER CUP</b>		ACAD REFERENCE NO.: 690M109JXAD-02X	
		DRAWN: C.B	DATE: December 18, 2020
CHECKED:		DATE:	
SCALE: 2:1	SHEET 1 OF 1		
DRAWING NUMBER: 690M109JXAD-02X			ISSUE
PART NUMBER: 690M109J1AD-021			1



THIS SERIES FULLY CONFORMS TO  
THE EUROPEAN UNION DIRECTIVES  
2011/65/EU FOR RoHS COMPLIANCY.

**EDAC** INC  
TORONTO, ONTARIO  
CANADA  
YOUR CONNECTION TO QUALITY & SERVICE

THESE DRAWINGS AND SPECIFICATIONS  
ARE THE PROPERTY OF EDAC INC., AND  
SHALL NOT BE REPRODUCED, OR COPIED  
OR USED AS THE BASIS FOR THE  
MANUFACTURE OR SALE OF APPARATUS  
WITHOUT WRITTEN PERMISSION.