


TOLERANCE UNLESS OTHERWISE SPECIFIED			
.X	±0.25		
.XX	±0.13		


.XXX ±0.05


THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.




ISSUE NUMBER ORIGINAL







THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



NOTE:

ELECTRICAL SPECIFICATIONS:

VOLTAGE RATING: 30V MAX. **CURRENT RATING:** 1.8A **CONTACT RESISTANCE:** $30m\Omega$ MAX. **INSULATOR RESISTANCE:** $100M\Omega$ min. DIELECTRIC WITHSTANDING VOLTAGE: 100V AC **OPERATING TEMPERATURE:** -25°C ~ 85°C

MATERIAL & FINISH:

JACKET: STAINLESS STEEL, T=0.30, NICKEL PLATING SHELL: COPPER ALLOY, T=0.30, NICKEL PLATING

HOUSING: PBT, WHITE IN COLOUR, UL94V-0

CONTACTS: COPPER ALLOY, T=0.20, 15µ" GOLD PLATING

690 SERIES RECEPTACLES USB 3.0 TYPE-A CABLE END SOLDER CUP



EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

ACAD REFERENCE NO.: 690M109JXAD-02X		
DRAWN: C.B	DATE: December	18, 2020
CHECKED:	DATE:	
SCALE: 2:1	SHEET 1 OF	1
DRAWING NUMBER: 690M109 IXAD-02X		ISSLIE

DRAWING NUMBER: 090W109JXAD-02X ISSUE 690M109J5AD-020 PART NUMBER: