		HIS IS A C.A.D. GENERATED DRAWING O NOT MAKE MANUAL REVISIONS TO M.	ASTER.	ISSUE NUMBER	1
			9.30]
SO T=0.50		x 0 1.10 (2x) − +0.02 15.50 0.00 − 17.50 − NOTE:	4.00		
		ELECTRIC CURRENT VOLTAGE CONTACT DIELECTR INSULATC A) B) OPERATIN	RATING: RESISTANCE: NC WITHSTANDING VOLTAG OR RESISTANCE: UNMATED	0.5A 40V 10mΩ MAX. E: 500V AC/ 1 MINUT 100MΩ min. @ 500 VI 10M min. @ 150 VDC -20°C~85°C -20°C~65°C	/DC
	690 SERIES RECEPT	ACAD REFERENCE NO.: 6940	UL94V-0		
THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.	TYPE-A MID-MO EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC., AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS	CHECKED: SCALE: 2:1 DRAWING NUMBER: 694C115	DATE: SHEET 1 OF 1 9-X53-011 IS	