


6.18

2.25








THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER ORIGINAL



NOTE:

ELECTRICAL SPECIFICATIONS:

CURRENT RATING: 0.5A **VOLTAGE RATING:** 40V

CONTACT RESISTANCE: 10mΩ MAX.

DIELECTRIC WITHSTANDING VOLTAGE: 500V AC/ 1 MINUTE

INSULATOR RESISTANCE:

A) UNMATED $100M\Omega$ min. @ 500 VDC B) MATED 10M min. @ 150 VDC

OPERATING TEMPERATURE: -20°C~85°C STORAGE TEMPERATURE: -20°C~65°C

MATERIAL & FINISH:

SHELL: COPPER ALLOY, NICKEL PLATED **HOUSING:** LCP, BLACK IN COLOUR, UL94V-0 CONTACTS: COPPER ALLOY, 30µ" GOLD PLATED

690 SERIES RECEPTACLES HDMI TYPE-A R/ANGLE SMT - STANDARD



EDAC INC TORONTO, ONTARIO CANADA

2.00 ±0.10

1.00 ±0.10

5.95

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

	ACAD REFERENCE NO.: 694D119-X65-011		
	DRAWN: C.B	DATE: December	30, 2020
	CHECKED:	DATE:	
	SCALE: 2:1	SHEET 1 OF	1
	DRAWING NUMBER: 604D410 V65 011		ICCLIE

DRAWING NUMBER: 694D119-X65-011 ISSUE PART NUMBER: 694D119-665-011