**Mounting Option** .344 (8.74) Offset Card Guides **Contact Detail** Wire Wrap .046x.014(1.17x0.36) - Tail LG=.495(12.57) .156 [3.96] Contact Spacing x .200 [5.08] Row Spacing 4.366[110.90] 4.220 [107.19] 0.343[8.71] 0.473[12.01] .175 [4.45] Point of Contact (Measured from bottom of Card Slot) EDRG

## **See Accompanying Pages for:**

- **Contact Bend Details**
- **Mounting Options**
- **Features and Specifications**

807 Series High Temp Card Edge Connector Part Number: 807-026-541-168



Card Slot Accepts .054 [1.37] to .070 [1.78] Thick P.C. Board

| acad reference SECTADING ASSAR |                  |        |  |  |  |
|--------------------------------|------------------|--------|--|--|--|
| DRAWN: J.LEE                   | DATE: AUG. 11/09 |        |  |  |  |
| CHECKED:                       | DATE:            |        |  |  |  |
| SCALE: NTS                     | SHEET '          | 1 OF 4 |  |  |  |
| DRAWING NUMBER                 |                  | ISSUE  |  |  |  |
| 807 Assembly                   |                  | 1      |  |  |  |





ISSUE NUMBE

ORIGINAL



## **Features**

- CSA Approved and UL Recognized
- .156 (3.96) Contact Spacing x .200 (5.08) Row Spacing
- Accepts .062 (1.57) Nominal Thickness P.C. Board
- Low Profile Insulator Body .473 (12.01), with Card Guides
- Contact Termination Options include P.C. Tail, Wire Hole, Wire Wrap, 90 Degree & Extender Board Bends
- Single or Dual Row Configurations
- Large Variety of Mounting Options
- Pre-assembled Card Guides Available
- Accepts Between Contact and In-Contact Polarizing Keys

## **Specifications**

- Insulator Material: DAP
- Contact Material: Copper, Nickel, Tin Alloy CA-725
- Contact Plating: Gold on the Mating Area, Tin on the Contact Tails, Nickel Underplate
- Current Rating: 5 Amperes Continuous
- Contact Resistance: 10 Milliohms Maximum
- Dielectric Withstanding Voltage: 1800 V AC rms at Sea Level Between Adjacent Contacts
- Insulation Resistance: 5000 Megohms Minimum
- Operating Temperature: -65 to +165 °C
- Insertion Force: 16 oz (4.45 N) Maximum per Contact Pair when Tested with a .070 (1.78) Thick Gauge
- Withdrawal Force: 1 oz (0.28 N) Minimum per Contact Pair when Tested with a .054 (1.37) Thick Gauge

| 807 Series High Temp Card Edge Connector<br>Features and Specifications |  | ACAD REFERENCE NO. 807 ENG MASTER |             |          |          |
|---|--|-----------------------------------|-------------|----------|----------|
|   |  | DRAWN:                            | J.LEE       | DATE: AU | G. 11/09 |
|   |  | CHECKE                            | ):          | DATE:    |          |
| EDAC INC  | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC., AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE | SCALE:                            | NTS         | SHEET .  | 4 OF 4   |
| TORONTO, ONTARIO  |  | DRAWING                           | NUMBER      |          | ISSUE    |
| YOUR CONNECTION TO QUALITY & SERVICE                                    | MANUFACTURE OR SALE OF APPARATUS   | 8                                 | 07 Assembly |          | 1        |