






ITEM NO.	DESCRIPTION	QTY.
1	HOUSING	1
2	MAGNET	2
3	POGO PIN	7

REVISIONS			
REV.	DESCRIPTION	DATE	BY
1	ORIGINAL	DRAWN DATE	



SPECIFICATIONS
 CURRENT RATING: 3A
 VOLTAGE RATING: 12V
 WITHSTANDING VOLTAGE: 500V
 INSULATION RESISTANCE: 1000MΩ MIN FOR 1 MIN
 CONTACT RESISTANCE: 50mΩ MAX
 TEMPERATURE RANGE: -25°C TO 80 °C

INSULATOR MATERIAL: HTN
 INSULATOR COLOR: BLACK
 CONTACT MATERIAL: BRASS
 CONTACT PLATING: 5μ" GOLD PLATING
 MAGNET MATERIAL: N52
 MATING CYCLES: 10000



NOTE:IR REFLOW AND WAVE SOLDERING NOT RECOMMENDED AS THE PROCESSES CAN DEMAGNETIZE THE CONNECTOR MAGNETS.

		DRAWN BY		V.K.		FEMALE CONNECTOR, RECTANGULAR, 2.2MM PITCH, 7 POSITIONS					
		DRAWN DATE		08/06/2025							
		CHECKED BY		R.S.M.							
		CHECK DATE		08/06/2025		PART NUMBER		MPF-VA0-107-2P05-A00			
RoHS COMPLIANT	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC, AND SHALL NOT BE REPRODUCED , OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	TOLERANCES		ALL DIMENSIONS AND TOLERANCES IN MM		MATERIAL				SIZE	A
		.X	±0.3					REVISION			
		.XX	±0.2								
		.XXX	±0.1								
						SCALE	3:1	SHEET	1	OF	1