


## USB 2.0 TYPE-A RECEPTACLES - RIGHT ANGLE SMT

### Features:


- Up to 480 Mbps communication speed for standard USB 2.0
- Industry standard plug and play technology - 'Hot Pluggable'
- Compatible with synchronous and asynchronous data transfer
- Data and power combined in one small package
- RoHS compliant



### Specifications:

Insulator Material	Thermoplastic UL-94V-0
Contact Material	Copper alloy
Contact Plating	Nickel under plating with Gold plating on contact areas and Tin plating on tails
Shell Material	Brass with Nickel plating
Insertion Force	35N maximum
Withdrawal Force	10N minimum

### EXAMPLE PART NUMBER: 690J104-667-210



#### Series:

690J Receptacle

#### Connector Type:

104 USB 2.0 Type-A

#### Contact Plating:

2 Gold Flash

6 30µ" Gold

#### Contact Code / Mounting Orientation:

6 Right Angle SMT

#### Mounting Option:

7 Plastic Posts & 2 Through Hole Grounding Tabs

#### Connector Option:

2 No Tabs on Leading Edge

#### Material:

1 LCP

#### Insulator Color:

0 White / Natural - (Not Available with Mounting Option 8)

1 Black

#### Ordering Code Notes:

Not all part numbers deriving from this ordering guide will be available.

Some may be available upon request. Please first consult the website, if the connector is not readily available then please contact EDAC's customer service for further inquiries.